

AD7013MTL



The Dino-Lite AD7013MTL has a 5 megapixel sensor for crystal clear images, even under higher magnification. Because of the very high resolution, the AD7013MTL is the ideal solution for displaying microscopic images on large screens or using the microscopic images for printing.



The AD series are equipped with exchangeable caps for even more flexibility. The long working distance of up to 15 cm enables the possibility to work under the microscope.

Additional Info

- Dino-Lite Range: Dino-Lite Long Working Distance
- Resolution: High (5 Megapixel)
- Magnification: Low/medium (10x-90x)
- Interface: USB 2.0
- Working Distance: Long
- Price Range (excl. VAT): €550,00 - €750,00
- Light/ LED type: White
- ESD Safe: Yes

- Polarizer: No
- Housing: Metal housing
- Special feature: No
- Dino-Lite Range: Dino-Lite Long Working Distance
- Light/ LED type: White
- Number of LEDs: 8
- LED on/off switchable: Yes
- Infrared filter: IR cut-filter >650 nm
- Diffuser available: No
- Emission filter: No
- Polarizer: No
- Magnification: 20-90x
- Macro zoom: No
- Working Distance: Long
- Resolution: 5 Megapixel (2592x1944)
- Maximum Frame rate: 30 fps
- Interface: USB 2.0
- Housing material: Metal housing
- Magnification lock: No
- Measurement: Yes
- Calibration: Yes
- Microtouch sensor: Yes
- ESD Safe: Yes
- Special feature: No
- Package contents: Microscope, Carry pouch, Open and closed cap, Software CD, Calibration target, User manual
- Price Range: €550,00 - €750,00

- **Details**

- Dino-Lite range: Dino-Lite Long Working Distance

- **Lighting**

- Light/ LED type: White
- Number of LEDs: 8
- LED on/off switchable: Yes
- Infrared filter: IR cut-filter >650 nm
- Diffuser available: No
- Emission filter: No
- Polarizer: No

- **Optics**

- Magnification: 20-90x
- Macro zoom: No
- Working distance: Long
- Lens type: Glass with anti-reflection coating

- **Sensor**

- Sensor type: CMOS
- Resolution: 5 Megapixel (2592x1944)
- Maximum frame rate: 30 fps

- **Compatibility**

- Interface: USB 2.0
- Operating system: Windows XP, Vista, 7, 8 & 10, MacOS 10.9 and up
- Included software: DinoCapture 2.0 (Windows), DinoXcope (Mac OS)
- Supported image formats (Windows): BMP, GIF, PNG, JPG, TIF, RAS, PNM, TGA, PCX, MNG, WBMP, JP2, JPC, PGX
- Supported video formats (Windows): WMV, FLV, SWF
- Supported image formats (MacOS): JPEG, PNG
- Supported video formats (MacOS): MOV
- Imaging standards: DirectShow, UVC

- **Housing**

- Housing material: Metal housing
- Magnification lock: No
- Dimensions: 10.5cm (L) x 3.2cm (D)
- Weight: 140g
- Cable length: 1.8m

- **Features**

- Special feature: No
- Measurement: Yes
- Calibration: Yes
- Microtouch sensor: Yes
- ESD safe: Yes

- **Information**

- Package contents: Microscope, Carry pouch, Open and closed cap, Software CD, Calibration target, User manual
- Warranty information: 2 years European warranty
- Regulatory approval: CE, FCC, ROHS
- Price range: €550,00 - €750,00
- Working distance/ field of view/ depth of field:

Magnification Rate	Working Distance	Field of View(x)	Field of View(y)	Depth of Field
20	160.5	19.8	14.9	6
Listed values may differ slightly				Unit = mm

Magnification Rate	Working Distance	Field of View(x)	Field of View(y)	Depth of Field
30	110.4	13.2	9.9	3.4
40	86.7	9.9	7.4	2.2
50	73.6	7.9	5.9	1.65
60	65.7	6.6	5.0	-
70	60.8	5.7	4.2	-
80	57.8	5.0	3.7	-
90	56.1	4.4	3.3	0.8

Listed values may differ slightly

Unit = mm

PDF generated on: 04-04-2019