


AM4515ZTL - Edge



The Dino-Lite Edge models provide superior image quality and a high level of flexibility due to the adaptable cap design. The built-in adjustable polarizer reduces glare and reflection on shiny objects.



With the built-in automatic magnification reading (AMR), measurements can be performed easily and quickly. Different caps are supplied with the microscope making the Dino-Lite Edge the perfect choice for any professional application. Together with the long working distance of up to 23 centimetres the AM4515ZTL is the ideal choice in situations, where real time images are vital, such as working on PCB's or other miniature objects.

Additional Info

- Dino-Lite Range: Dino-Lite Long Working Distance
- Resolution: Medium (800x600 - 1.3 Megapixel)
- Magnification: Low/medium (10x-140x)
- Interface: USB 2.0
- Working Distance: Long
- Price Range (excl. VAT): €550,00 - €750,00

- Light/ LED type: White
- ESD Safe: No
- Polarizer: Yes
- Housing: Composite/plastic housing
- Special feature: Aut. Magn. reading
- Dino-Lite Range: Dino-Lite Long Working Distance
- Light/ LED type: White
- Number of LEDs: 8
- LED on/off switchable: Yes
- Infrared filter: IR cut-filter >650 nm
- Diffuser available: Yes (N3C-D included)
- Emission filter: No
- Polarizer: Yes, linear
- Magnification: 10-140x
- Macro zoom: No
- Working Distance: Long
- Resolution: 1.3 Megapixel (1280x1024)
- Maximum Frame rate: 30 fps
- Interface: USB 2.0
- Housing material: Composite/ plastic housing
- Magnification lock: Yes
- Measurement: Yes
- Calibration: Yes
- Microtouch sensor: Yes
- ESD Safe: No
- Special feature: Aut. Magn. reading
- Package contents: Microscope, Carry pouch, Software CD, Calibration target, User manual, N3C-O- Open cap, N3C-C- Closed cap, N3C-D- Diffuser cap, N3C-E- Extension cap, N3C-L- Long cap, N3C-S- Side light cap
- Price Range: €550,00 - €750,00

- **Details**

- Dino-Lite range: Dino-Lite Long Working Distance

- **Lighting**

- Light/ LED type: White
- Number of LEDs: 8
- LED on/off switchable: Yes
- Infrared filter: IR cut-filter >650 nm
- Diffuser available: Yes (N3C-D included)
- Emission filter: No
- Polarizer: Yes, linear

- **Optics**

- Magnification: 10-140x
- Macro zoom: No

- Working distance: Long
- Lens type: Glass with anti-reflection coating
- **Sensor**
 - Sensor type: CMOS
 - Resolution: 1.3 Megapixel (1280x1024)
 - Maximum frame rate: 30 fps
- **Compatibility**
 - Interface: USB 2.0
 - Operating system: Windows XP, Vista, 7, 8 & 10, MacOS 10.9 and up
 - Included software: DinoCapture 2.0 (Windows), DinoXcope (Mac OS)
 - Supported image formats (Windows): BMP, GIF, PNG, JPG, TIF, RAS, PNM, TGA, PCX, MNG, WBMP, JP2, JPC, PGX
 - Supported video formats (Windows): WMV, FLV, SWF
 - Supported image formats (MacOS): JPEG, PNG
 - Supported video formats (MacOS): MOV
 - Imaging standards: DirectShow, UVC
- **Housing**
 - Housing material: Composite/ plastic housing
 - Magnification lock: Yes
 - Dimensions: 10.5cm (L) x 3.2cm (D)
 - Weight: 105g
 - Cable length: 1.8m
- **Features**
 - Special feature: Aut. Magn. reading
 - Measurement: Yes
 - Calibration: Yes
 - Microtouch sensor: Yes
 - ESD safe: No
- **Information**
 - Package contents:
Microscope, Carry pouch, Software CD, Calibration target, User manual, N3C-O- Open cap, N3C-C- Closed cap, N3C-D- Diffuser cap, N3C-E- Extension cap, N3C-L- Long cap, N3C-S- Side light cap
 - Warranty information: 2 years European warranty
 - Regulatory approval: CE, FCC, ROHS
 - Price range: €550,00 - €750,00
 - Working distance/ field of view/ depth of field:

Magnification Rate	Working Distance*	Field of View(x)	Field of View(y)	Depth of Field
10	234.5	39.0	31.2	12
20	112.5	19.5	15.6	4.5
30	72.5	13.0	10.4	3.1
40	54.5	9.8	7.8	1.8
50	43.5	7.8	6.2	1.2
60	37.5	6.5	5.2	0.9
70	33.7	5.6	4.5	0.6
80	31.3	4.9	3.9	0.5
90	29.9	4.3	3.5	0.37
100	29.2	3.9	3.1	0.28
110	29.1	3.5	2.8	0.22
120	29.3	3.3	2.6	0.17
130	29.8	3.0	2.4	0.12
140	30.5	2.8	2.2	0.09
Listed values may differ slightly	* Without front cap			Unit = mm

PDF generated on: 04-04-2019